| Kingdom of Bahrain | | مملكة البحرين |
|--|----------|-----------------------------|
| Electricity & Water Authority | | هيئة الكهرباء والماء |
| Electricity & Water Conservation Directorate | Z. B. B. | إدارة ترشيد الكهرياء والماء |
| | | |

THERMAL INSULATION IMPLEMENTATION MODIFICATION FORM

| ate | Approved | _ | | | | |
|--------------|---------------------------------------|------------------------------|----------------------------|----------------------|----------------|------------------------|
| | Owner | | □ Eng | ineering | Office | |
| | Insulation Materials in Ro | of | □ Insu | lation M | Iaterials in v | valls |
| • | Glass Type Thermal Transmittance(U-v | value) for Ro | | s Area | | |
| Sr. No. | Description of materials used in Roof | Density kg/m ³ | Thickness (I) m | r <u>m.k</u> w | R m².k w | Notes |
| 1- | | | | | | |
| 2- | | | | | | |
| 3- | | | | | | |
| 4- 5- | | | | | | |
| 6- | | | | | | |
| 7- | | | | | | |
| 8- | | | | | | |
| 9- | | | | | | |
| | Total thermal resistances for m | aterials used | in Roof (R _T): | | | |
| | U-Value = W/m. | ² °C | | | | |
| | t's Name | Incharge E Name & Si | 0 | | Engineeri | ng Office Signature |

| Kingdom of Bahrain | مملكة البحرين |
|--|-----------------------------|
| Electricity & Water Authority | هيئة الكهرياء والماء |
| Electricity & Water Conservation Directorate | إدارة ترشيد الكهرياء والماء |
| | |

• Thermal Transmittance (U-Value) for Air-conditioned floors/ceilings exposed to non air-conditioned spaces

| Sr. No. | Description of materials used | Density kg/m ³ | Thickness (I) m | r <u>m.k</u> w | R m².k w | Notes | | |
|------------|--|------------------------------|-----------------------|----------------------|----------------|-------|--|--|
| 1- | | | | | | | | |
| 2- | | | | | | | | |
| 3- | | | | | | | | |
| 4- | | | | | | | | |
| 5- | | | | | | | | |
| 6- | | | | | | | | |
| 7- | | | | | | | | |
| 8- | | | | | | | | |
| 9- | | | | | | | | |
| 10- | | | | | | | | |
| 11- | · | | | | | | | |
| 12- | | | | | | | | |
| 13- | | | | | | | | |
| | Total thermal resistance for materials used in Wall (R _T): | | | | | | | |

| W/m. ² °C |
|----------------------|
| |

| Client's Name & Signature | Incharge Engineer Name & Signature | Engineering Office Stamp & Signatur | |
|------------------------------|------------------------------------|-------------------------------------|--|
| | | | |
| Electricity & Water Aut | hority Approval | Date of Approval | |

| Kingdom of Bahrain | مملكة البحرين |
|--|-----------------------------|
| Electricity & Water Authority | هيئة الكهرباء والماء |
| Electricity & Water Conservation Directorate | إدارة ترشيد الكهرباء والماء |
| | |

• Thermal Transmittance (U-Value) for external Walls with Blocks

| Sr. No. | Description of materials used | Density kg/m³ | Thickness (I) m | r <u>m.k</u> w | R <u>m².k</u> w | Notes | |
|------------|--|------------------|-----------------------|----------------------|-----------------------|-------|--|
| 1- | | | | | | | |
| 2- | | | | | | | |
| 3- | | | | | | | |
| 4- | | | | | | | |
| 5- | | | | | | | |
| 6- | | | | | | | |
| 7- | | | | | | | |
| 8- | | | | | | | |
| 9- | | | | | | | |
| 10- | | | | | | | |
| 11- | | | | | | | |
| 12- | | | | | | | |
| 13- | | | | | | | |
| | Total thermal resistance for materials used in Wall (R _T): | | | | | | |

| | | (-1) | | |
|------------------------------|----------------------|---------------------------------------|------|-----------------------------|
| U-Value = | W/m. ² °C | | | |
| Client's Name & Signature | | Incharge Engineer Name & Signature | _ | ering Office & Signature |
| Electricity & Wate | r Authority A | pproval | Date | of Approval |

| Kingdom of Bahrain | | مملكة البحرين |
|--|---|-----------------------------|
| Electricity & Water Authority | | هيئة الكهرياء والماء |
| Electricity & Water Conservation Directorate | 2 | إدارة ترشيد الكهرباء والماء |
| | | |

• Thermal Transmittance (U-Value) for Concrete/ Shear Walls

| Sr. No. | Description of materials used | Density kg/m ³ | Thickness (I) m | r <u>m.k</u> w | R m².k w | Notes |
|------------|-------------------------------|------------------------------|-----------------------|-------------------------------|----------------|-------|
| 1- | | | | | | |
| 2- | | | | | | |
| 3- | | | | | | |
| 4- | | | | | | |
| 5- | | | | | | |
| 6- | | | | | | |
| 7- | | | | | | |
| 8- | | | | | | |
| 9- | | | | | | |
| 10- | | | | | | |
| 11- | | | | | | |
| 12- | | | | | | |
| 13- | | | | | | |
| | Total thermal resistance for | materials 1 | used in Wall | $(\mathbf{R}_{\mathrm{T}})$: | | |

| U-Value = | W/m. ² °C | | | | I |
|------------------------------|----------------------|--------------------------|---|------|-----------------------------|
| Client's Name & Signature | | Incharge E Name & Sig | _ | _ | ering Office & Signature |
| Electricity & Wat | er Authority A | approval | | Date | of Approval |

• Thermal Transmittance (U-Value) for External Columns

| Sr. No. | Description of materials used | Density kg/m ³ | Thickness (I) m | r <u>m.k</u> w | R <u>m².k</u> w | Notes |
|------------|-------------------------------|------------------------------|-----------------------|----------------------------|-----------------------|-------|
| 1- | | | | | | |
| 2- | | | | | | |
| 3- | | | | | | |
| 4- | | | | | | |
| 5- | | | | | | |
| 6- | | | | | | |
| 7- | | | | | | |
| 8- | | | | | | |
| 9- | | | | | | |
| 10- | | | | | | |
| 11- | | | | | | |
| 12- | | | | | | |
| 13- | | | | | | |
| | Total thermal resistance for | materials ı | used in Wall | (R _T): | | |

| | | (-1) | | |
|------------------------------|----------------------|---------------------------------------|------|-----------------------------|
| U-Value = | W/m. ² °C | | | |
| Client's Name & Signature | | Incharge Engineer Name & Signature | _ | ering Office & Signature |
| Electricity & Wate | er Authority A | pproval | Date | of Approval |

| Kingdom of Bahrain | مملكة البحرين |
|--|-----------------------------|
| Electricity & Water Authority | هيئة الكهرباء والماء |
| Electricity & Water Conservation Directorate | إدارة ترشيد الكهرباء والماء |

• Thermal Transmittance (U-Value) for External Beams

| Sr. No. | Description of materials used | Density kg/m³ | Thickness (I) m | r <u>m.k</u> w | R <u>m².k</u> w | Notes | |
|------------|--|------------------|-----------------------|----------------------|-----------------------|-------|--|
| 1- | | | | | | | |
| 2- | | | | | | | |
| 3- | | | | | | | |
| 4- | | | | | | | |
| 5- | | | | | | | |
| 6- | | | | | | | |
| 7- | | | | | | | |
| 8- | | | | | | | |
| 9- | | | | | | | |
| 10- | | | | | | | |
| 11- | | | | | | | |
| 12- | | | | | | | |
| 13- | | | | | | | |
| | Total thermal resistance for materials used in Wall (R _T): | | | | | | |

Total thermal resistance for materials used in Wall (R_T):

U-Value = W/m.² °C

Client's Name Incharge Engineer Engineering Office & Signature Name & Signature Stamp & Signature

Electricity & Water Authority Approval

| Kingdom of Bahrain | مملكة البحرين |
|--|-----------------------------|
| Electricity & Water Authority | هيئة الكهرباء والماء |
| Electricity & Water Conservation Directorate | إدارة ترشيد الكهرباء والماء |

• Thermal Transmittance (U-Value) for Spandrel Area of Curtain Wall

| Sr. No. | Description of materials used | Density kg/m ³ | Thickness (I) m | r <u>m.k</u> w | R <u>m².k</u> w | Notes |
|------------|--|------------------------------|-----------------------|----------------------|-----------------------|-------|
| 1- | | | | | | |
| 2- | | | | | | |
| 3- | | | | | | |
| 4- | | | | | | |
| 5- | | | | | | |
| 6- | | | | | | |
| 7- | | | | | | |
| 8- | | | | | | |
| 9- | | | | | | |
| 10- | | | | | | |
| 11- | | | | | | |
| 12- | | | | | | |
| 13- | | | | | | |
| | Total thermal resistance for materials used in Wall (R _T): | | | | | |

Total thermal resistance for materials used in vian (XI).

| U-Value = | W/m. ² °C | | |
|------------------------------|----------------------|---------------------------------------|---|
| Client's Name & Signature | | Incharge Engineer Name & Signature | Engineering Office Stamp & Signature |
| Electricity & Water | er Authority A | pproval | Date of Approval |

| Kingdom of Bahrain | | مملكة البحرين |
|--|-------------------|-----------------------------|
| Electricity & Water Authority | | هيئة الكهرباء والماء |
| Electricity & Water Conservation Directorate | The second second | إدارة ترشيد الكهرياء والماء |
| | | |

$Thermal\ Transmittance\ (U\text{-}Value)\ for\ walls\ of\ light\ wells/shafts/voids$

| Sr. No. | Description of materials used in Walls | Density kg/m³ | Thickness (I) m | r <u>m.k</u> w | R <u>m².k</u> w | Notes |
|------------|--|------------------|-----------------------|----------------------|-----------------------|-------|
| 1- | | | | | | |
| 2- | | | | | | |
| 3- | | | | | | |
| 4- | | | | | | |
| 5- | | | | | | |
| 6- | | | | | | |
| 7- | | | | | | |
| 8- | | | | | | |
| 9- | | | | | | |
| 10- | | | | | | |
| 11- | | | | | | |
| 12- | | | | | | |
| 13- | | | | | | |
| | Total thermal resistance for materials used in Wall (R _T): | | | | | |

| Total the | rmal resistance | for materials used in Wall (R _T): | | |
|------------------------------|----------------------|---|------|-----------------------------|
| U-Value = | W/m. ² °C | | | |
| Client's Name & Signature | | Incharge Engineer Name & Signature | _ | ering Office & Signature |
| Electricity & Wate | er Authority A | pproval | Date | of Approval |

| Kingdom of Bahrain | | مملكة البحرين |
|--|---|-----------------------------|
| Electricity & Water Authority | | هيئة الكهرباء والماء |
| Electricity & Water Conservation Directorate | 2 | إدارة ترشيد الكهرياء والماء |
| | | |

• Thermal Transmittance (U-Value) for

(specify the type of wall)

| Sr. No. | Description of materials used in Exterior Walls | Density kg/m ³ | Thickness (I) m | r <u>m.k</u> w | R m².k w | Notes |
|------------|--|------------------------------|-----------------------|----------------------|----------------|-------|
| 1- | | | | | | |
| 2- | | | | | | |
| 3- | | | | | | |
| 4- | | | | | | |
| 5- | | | | | | |
| 6- | | | | | | |
| 7- | | | | | | |
| 8- | | | | | | |
| 9- | | | | | | |
| 10- | | | | | | |
| 11- | | | | | | |
| 12- | | | | | | |
| 13- | | | | | | |
| | Total thermal resistance for materials used in Wall (R _T): | | | | | |

| | | | ` | l | _ |
|------------------------------|----------------------|---------------------------------------|---|--------|-----------------------------|
| U-Value = | W/m. ² °C | | | | |
| Client's Name & Signature | | Incharge Engineer Name & Signature | | _ | ering Office & Signature |
| Electricity & Water | · Authority A | nnroval | | Date (| of Approval |

| Kingdom of Bahrain | | مملكة البحرين |
|--|--|-----------------------------|
| Electricity & Water Authority | | هيئة الكهرباء والماء |
| Electricity & Water Conservation Directorate | S. S | إدارة ترشيد الكهرباء والماء |
| | | |

Glass Selection Details

| _ | | | | | | | |
|---|-----------------|-----------------|--------------|-----------|--------------------------|-------------------------|---------|
| | Location | Windows & Doors | Curtain Wall | Sky Light | Total Glass Area (M²) | Total Surface Area (M²) | Glass % |
| | Glass Area (M²) | | | | | | |

| | GLASS MAKE/DESCRIPTION/COATING SURFCE # | | TH | THICKNESS (mm) | | | SHADING |
|------------------|---|-------------|----------------|----------------|----------------|---------------------------------|------------------|
| LOCATION | OUTER GLASS | INNER GLASS | OUTER GLASS | AIR SPACE | INNER GLASS | VALUE (W/M ^{2 O} C) | COEFFICIENT (SC) |
| WINDOWS & DOORS | | | | | | | |
| CURTAIN WALLS | | | | | | | |
| SKY LIGHT | | | | | | | |

I hereby state that all information in the attached tables and documents is correct and I confirm that I will comply with Thermal Insulation Order no. (8 /99) for the construction of this building.

| Client's Name & Signature | Incharge Engineer Name & Signature | Engineering Office Stamp & Signature |
|------------------------------|------------------------------------|---|
| Electricity & Water | Authority Approval | Date of Approval |